


Tolerances		Revisions									
1-20=+/-0,2	20-30=+/-0,3	30-40=+/-0,4	40-50=+/-0,5								
50-100=+/-0,75	100-300=+/-1,5	Angles=+/-1									
Dimensions are in Millimeters		<table border="1"> <thead> <tr> <th>Description/Approver/Date</th> <th>Approved M.H.</th> <th>Checked M.H.</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td>Drawn S.A.</td> <td>Date</td> </tr> </tbody> </table>		Description/Approver/Date	Approved M.H.	Checked M.H.	Date			Drawn S.A.	Date
Description/Approver/Date	Approved M.H.	Checked M.H.	Date								
		Drawn S.A.	Date								
NOTES (plating thickness in micro-inches): 1. Per QQ-B-626 2. Per QQ-S-764 3. Per QQ-C-530 4. Per QQ-B-750 5. Per MIL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike											



1. Connector : IPX	Description	
2. Cable: 50ohm Micro Coax 1.13mm	Cable Assembly, IPX right angle crimp jack to IPX right angle crimp jack	
3. Connector : IPX	with 50ohm micro 1.13mm coax cable, 4 inches in length.	
4.	Scale	2:1
5.	Drawing No.	CB1.13-2IPX-4"
6.	File Name	CB1.13-2IPX-4"
7.		
8.		



**Lighthouse Technologies, Inc.**  
 9511 Ridgehaven Ct, Suite B  
 San Diego, CA 92123  
 Part Number:  
 CB1.13-2IPX-4"