


Tolerances		Revisions													
1-20=+/-0,2	20-30=+/-0,3	30-40=+/-0,4	40-50=+/-0,5												
50-100=+/-0,75	100-300=+/-1,5	Angles=+/-1													
Dimensions are in Millimeters		<table border="1"> <thead> <tr> <th>Description/Approved/Date</th> <th>Approved M.H.</th> <th>Checked M.H.</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Drawn S.A.</td> <td>Date</td> </tr> </tbody> </table>		Description/Approved/Date	Approved M.H.	Checked M.H.	Date							Drawn S.A.	Date
Description/Approved/Date	Approved M.H.	Checked M.H.	Date												
		Drawn S.A.	Date												
NOTES (plating thickness in micro-inches): 5. Per MILL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over 9. Nickel pl. 100 min. over 10. Per QQ-P-35 11. Gold pl. 30 min. over 1. Per QQ-B-626 2. Per QQ-S-764 3. Per QQ-C-530 4. Per QQ-B-750 copper strike nickel pl. 50 min. over copper strike copper strike															



1. Connector : LTI-SASRF13GT-178	Description	
2. Cable: Micro Coax 50ohm 1.13mm micro coax	Cable Assembly, RP-SMA bulkhead crimp jack to IPX crimp jack,	
3. Connector : IPX	with 1.13mm double shielded 50ohm cable, 6 inches in length.	
4.	Scale	
5.	2:1	
6.	Drawing No.	
7.	File Name	
8.	CB1.13-IPX-SARF3GT-6in	



Lighthouse Technologies, Inc.
 9511 Ridgeway Ct, Suite B,
 San Diego, CA 92123
 Part Number:
 CB1.13-IPX-SARF3GT-6in