



Tolerances		Revisions													
1-20=+/-0.2	20-30=+/-0.3	30-40=+/-0.4	40-50=+/-0.5												
50-100=+/-0.75	100-300=+/-1.5	Angles=+/-1													
Dimensions are in Millimeters		<table border="1"> <thead> <tr> <th>Description/Approver/Date</th> <th>Approved M.H.</th> <th>Checked M.H.</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>Drawn S.A.</td> <td>Date</td> </tr> </tbody> </table>		Description/Approver/Date	Approved M.H.	Checked M.H.	Date							Drawn S.A.	Date
Description/Approver/Date	Approved M.H.	Checked M.H.	Date												
		Drawn S.A.	Date												
NOTES (plating thickness in micro-inches): 1. Per QQ-B-626 2. Per QQ-S-764 3. Per QQ-C-530 4. Per QQ-B-750 5. Per MIL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike															



1. Connector : IPX	Description	
2. Cable: 50ohm Micro Coax 1.32mm double shielded	Cable Assembly, IPX right angle crimp jack to IPX right angle crimp jack	
3. Connector : IPX	with 50ohm micro 1.32mm double shielded coax cable, 12 inches in length.	
4.	Scale	2:1
5.	Drawing No.	CB1.32D-2IPX-12"
6.	File Name	CB1.32D-2IPX-12"
7.	 <b>Lighthouse Technologies, Inc.</b> 9511 Ridgehaven Ct, Suite B San Diego, CA 92123 Part Number: CB1.32D-2IPX-12"	
8.		