


Tolerances		Revisions													
1-20=+/-0,2	20-30=+/-0,3	30-40=+/-0,4	40-50=+/-0,5												
50-100=+/-0,75	100-300=+/-1,5	Angles=+/-1													
Dimensions are in Millimeters		<table border="1"> <thead> <tr> <th>Description/Approver/Date</th> <th>Approved</th> <th>Checked</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td></td> <td>M.H.</td> <td>M.H.</td> <td></td> </tr> <tr> <td></td> <td></td> <td>Drawn</td> <td>S.A.</td> </tr> </tbody> </table>		Description/Approver/Date	Approved	Checked	Date		M.H.	M.H.				Drawn	S.A.
Description/Approver/Date	Approved	Checked	Date												
	M.H.	M.H.													
		Drawn	S.A.												
NOTES (plating thickness) 5. Per MIL-P-19468 In micro-inches: 6. Per ZZ-R-765 1. Per QQ-B-626 7. Per WW-T-799 2. Per QQ-S-764 8. Gold pl. 5 min. over 3. Per QQ-C-530 nickel pl. 50 min. over 4. Per QQ-B-750 copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike															



1. Connector : IPX	Description		
2. Cable: 50ohm RG-178	Cable Assembly, IPX right angle crimp jack to IPX right angle crimp jack		
3. Connector : IPX	with 50ohm RG-178, 8 inches in length.		
4.	Scale 2:1		
5.	Drawing No.		
6.	File Name		
7.	CBG-2IPX-8"		
8.			



Lighthouse Technologies, Inc.
 9511 Ridgeway Ct, Suite B
 San Diego, CA 92123
 Part Number:
 CBG-2IPX-8"