


Tolerances		Revisions													
1-20=+/-0.2	20-30=+/-0.3	30-40=+/-0.4	40-50=+/-0.5												
50-100=+/-0.75	100-300=+/-1.5	Angles=+/-1													
Dimensions are in Millimeters		<table border="1"> <thead> <tr> <th>Description/Approver/Date</th> <th>Approved</th> <th>Checked</th> <th>Date</th> </tr> </thead> <tbody> <tr> <td></td> <td>M.H.</td> <td>M.H.</td> <td></td> </tr> <tr> <td></td> <td></td> <td>Drawn</td> <td>S.A.</td> </tr> </tbody> </table>		Description/Approver/Date	Approved	Checked	Date		M.H.	M.H.				Drawn	S.A.
Description/Approver/Date	Approved	Checked	Date												
	M.H.	M.H.													
		Drawn	S.A.												
NOTES (plating thickness): 1. Per QQ-B-626 2. Per QQ-S-764 3. Per QQ-C-530 4. Per QQ-B-750 5. Per MIL-P-19468 6. Per ZZ-R-765 7. Per WW-T-799 8. Gold pl. 5 min. over nickel pl. 50 min. over copper strike 9. Nickel pl. 100 min. over copper strike 10. Per QQ-P-35 11. Gold pl. 30 min. over nickel pl. 50 min. over copper strike															



1. Connector : IPX	Description	
2. Cable: 50ohm RG-178	Cable Assembly, IPX right angle crimp jack to IPX right angle crimp jack	
3. Connector : IPX	with 50ohm RG-178, 12 inches in length.	
4.	Scale	2:1
5.	Drawing No.	
6.	File Name	CBG-2IPX-12"
7.		
8.		



Lighthouse Technologies, Inc.
 9511 Ridgehaven Ct, Suite B
 San Diego, CA 92123
 Part Number:
 CBG-2IPX-12"